



## Rust Sales, Inc.

2964 164 Ave. SE

Harwood, ND 58042

Toll Free: 800-478-7801

Outside U.S: 701-282-9194

Fax: 701-282-0099

www.rustsales.com



# The RSI BANDSPRAYER

...covers a lot of acres **FAST!**

- ACCURATE
- EASY TO USE
- LOW HP REQUIRED
- BAND or BROADCAST



## Easy Transport

Rear fold back design give a transport width of only 15 1/2' and transport height of 78"

## Hydraulic Wing Wheels



Minimize the back-up distance to unfold the sprayer into field position.



## True Track Guidance System

V-Guidance wheels with dual parallel linkage allow each wing gang to track rows accurately.

## Unique Skid Design



Follows ground contour to ensure proper spray tip height. Comes with replaceable abrasion resistant shoe.

## SPECIFICATIONS

Models 3622, 3624, 2430

36 Row - 22" Spacing / 36 Row - 24" Spacing / 24 Row - 30" Spacing

### Frame

4 x 2 x 3/16" Cart  
4 x 4 x 1/4" Wing Tube  
2 x 2 x 3/16" Carrier Tube

### Hydraulics

3 tractor remotes required  
2" x 8" Dual Parallel Hyd. Wing Fold c/w Depth Stop  
3" x 8" Single Cylinder Hyd. Boom Height  
Hypro Hydraulic Centrifugal Spray Pump

### Tank

500 Gallon White Fiberglass Tank  
Front and Rear Sight Gauge  
15" Fillwell Lid  
Agitation Tube  
Front Deep Well Sump  
9 Gallon Hand Rinse Safety Tank w/Tool Compartment

### Axles

2" Dia. Spindle - 3500 Lbs. 6 Bolt Cart Hubs  
1" - 5/8" Dia. Spindle - 1400 Lbs. 4 Bolt Wing Hubs

### Tires

2 - 7.50 x 16 - 6 Ply Monorib Cart Tires w/ tube  
2 - 5.00 x 15 - 4 Ply Wing Implement Rib - Tubeless  
4 - 3 x 14 Solid V - Wheel w/ U-cut Integrated Bearing

### Spray Components

Banjo Polypropylene Fittings  
Black Rubber 200 psi hose  
Precision Fit Nozzles (Spraying Systems Compatible)  
Texas Remcor 1999-1 Atlas Triple Solenoids  
Raven 203 Boom Control System  
2" Bottom Fill  
Tip Pressure Sensing

### Jack

Screw type: 2000 lb Topwind

### Transport Dimensions

38' Over All Length  
15 - 1/2" Width  
78" Transport Height

### Skid

Greasable Pivot Point  
Replaceable Abrasion Resistant Shoe

Banjo is a registered trademark of Banjo Corp.  
Precision Fit is a registered trademark of Precision Fitting & Valve  
Texas Remcor is a registered trademark of Raven Ind.  
Hypro is a registered trademark of Hypro Co.  
Dosatron is a registered trademark of Dosatron International